



Aluminum- alloy.  
Colorless anodized.  
Suitable for single & double load cells structured platform scales.  
Recommended platform size: 600x600mm

Capacity	Accuracy	Part number	Resistance
50kg	C3	L6G- C3- 50kg- 3G6	350
100kg	C3	L6G-C3-100kg-3G6	350
300kg	C3	L6G-C3-300kg-3G6	350
500kg	C3	L6G-C3-500kg-3G6	350

### Specifications

Accuracy Class	OIML R60 C3	Temperature effect on span (%FS/10°C)	0.014
Rated output (mV/V)	2.0±0.2	Temperature effect on zero (%FS/10°C)	0.017
Combined error (%FS)	0.02	Temperature, compensated (°C)	-10~+40
Non-linearity (%FS)	0.017	Temperature, Operating (°C)	-35~+65
Non-repeatability (%FS)	0.01	Excitation, Recommended (V)	5~12(DC)
Creep (%FS/30min)	0.015	Excitation, Max.( V)	18(DC)
Input Resistance (Ω)	409±6 or 1065±15	Safe Overload (%FS)	150
Output Resistance (Ω)	350±3 or 1000±5	Ultimate Overload (%FS)	300
Insulation Resistance (MΩ)	≥5000(50VDC)	Protection Class	IP 65
Zero Balance (%FS)	2.0	Cable Length (m)	3
Off center load error (% , per OIML R 76)	0.02	Cable spec	6-wire shielded cable φ 6mm

Connections Red Input(+) Black Input(-) Green Output(+) White Output(-)  
Blue Sense(+) Yellow Sense(-) Transparence (shield)

### Outline Dimensions in mm(inches)

