


Technical Data Sheet

 GRUPO EPELSA Technical Data sheet		JUPITER					
Capacities	6kg	15kg	30kg	6/15kg	15/30kg	12kg (6.000d)	30kg (6.000d)
Division	2g	5g	10g	2/5g	5/10g	2g	5g
Minimum load	40g	100g	200g	40g	100g	40g	100g
Max. Tare	3.000g	9.995g	9.990g	3.000g	9.995g	3.000g	9.990g
General features 		Scale counter and hanging model, with thermal printer, label or both. Automatic go to zero, key to put to zero, and allows printing under minimum load according to calibration rules. Up to 10 scales interconnected through Ethernet, compatible with every model of the range in the same network. Connection through XDSL. RS232 communication port Connectable to PC, updates software version through RS232 and Ethernet					
DISPLAY 		Alphanumeric Display with Back Light. Two lines, showing WEIGHT, PRICE and AMOUNT. Indicators of TARA, zero, stability.... And other alphanumeric line to show article texts and Menus. Possibility of showing offers and publicity. Programmable intensity of the backlight of the Display. , Possibility of displaying offers and continuous publicity.					
KEYBOARD 		98 keyboard, 49 of them are direct PLUs and 49 function keys. It is possible to create 10 DIRECT CHARTS for a quick Access to the PLU. 10 active vendors, stand-by function for switching off the scale keeping active the server of communications. 12 Direct programmable keys for direct functions. 11 V10 scale can be supplied with a 66 keyboard.					
Programmable Data per PLU		Price of the article, description with a maximum of 1025 characters , fixed text with a maximum of 250 characters, family, packing date, expiration date, best before date, bar code, internal code and PLU, Tare, VAT, stepped price, article's sales offer, Direct PLU, EAN code.					
Memory		Microprocessor ARM/INTEL386 with 2/4 Mb RAM memory, Database (Standard version): <ul style="list-style-type: none"> ❖ Receipts/tickets: 10.000 ❖ Ticket lines: 20.000 ❖ Bitmap: size 12 KB (2 Bitmap possible) ❖ Countries: 50 ❖ Price changes: 200 					

	<ul style="list-style-type: none"> ❖ Memorized tares: 10 ❖ Merchandise: 30 ❖ VAT: 5 ❖ Bovine: 255 ❖ Text: 34 ❖ Bar codes: 14 ❖ Vendor direct keys: 10 ❖ Vendors: 141 ❖ Orders: 200 ❖ Formats: 80 ❖ Packing: 8.300 ❖ Descriptions: ~ 30.000 ❖ Articles: 10.000 ❖ Clients: 500
Thermal Printer (tickets) 	<p>Graphic printer with programmable speed between 80-140 mm/s. Logo printing, negatives, bar codes EAN 13, EAN 128, CODE 128. 5 headings and 5 legend lines, Option to select report receipt.</p>
Labels Printer 	<p>With the same characteristics as the ticket printer, labels configurable in size and availability of fields, with the possibility of printing on adhesive labels or on adhesive continuous paper.</p>
Interface	<p>Ethernet board 10/100 and RS 232 port. Interconnection with up to 10 scales via Ethernet, option for communication through the Electrical Network (CRE), connection to a scanner and a cash drawer. Connection to the HOST through Ethernet or serial cable RS-232</p>
Features 	<p>Digital load cell with incorporated microprocessor. Program re-loadable through serial cable or Ethernet utilizing FLASH memory. Clock for date and time maintenance. Automatic centring of texts, redirection of labeller and printer. Configurable language, grouping of items by family (99), up to 141 vendors, configurable vendor registration, vendor names stored in the equipment, up to 99 operations per ticket, totals separated by ARTICLES, FAMILIES, VENDORS, HOURLY TOTAL, DAILY and ACCUMULATED SALES, TICKET. PLUs, departments, items, vendors, and other lists. Different sale modes: TICKET, SUPER, TOTAL ORDER, PACKING SELF-SERVICE. Discount per line or over the total. Different levels of configurable MENU with possibility for password restriction. Selectable language. Review and reprinting of closed tickets, ticket storage in autonomous mode, ticket report in reduced or enlarged format.</p>
Operating Temperature	<p>-10° a +40°C</p>
Voltage	<p>220V. (+10%, -15%), (other voltage possible)</p>
Current Consumption	<p>Between 40 and 60w</p>
Frequency	<p>50 / 60 HZ</p>